

2002 SONY MOBILE PRODUCT GUIDE



XS-L1536 **15" Component Subwoofer**

- 15" Polypropylene Cone
- 1000W max input power (350W RMS)
- Santoprene Rubber Surround
- Dual Damper Suspension
- Gold-plated Binding Posts
- Small sealed/ported enclosure optimized
- 4Ω Voice Coil

- Indicates step-up

Specifications

Speaker	Woofer 38 cm (15 in.), cone type
Maximum input power	1,000 watts
Rated input power	350 watts
Impedance	4 ohms
Sensitivity	89 dB/W/m
Frequency response	18 – 1,500 Hz
Mass	Approx. 7.6 kg (16 lb. 12 oz.) per speaker
Supplied accessory	Parts for installation

Thiele/Small Parameters

Impedance	4Ω	Vas (Lit.)	204.1
d (mm)	340	Vas (Cu.ft)	6.13
d (inch)	13.4	Mms (g)	248.5
Rdc (Ω)	3.2	Lvc (mH)	1.3
Fs (Hz)	23.0	Xmax (mm)	4
Qts	0.42	Xmax (inch)	0.16
Qes	0.46	BL (Tm)	16.1
Qms	5.66	Enclosure vol. (Net)	(1.4 cu.ft)

Recommended Enclosure: Sealed type

XS-L1536
15" Component Subwoofer

Dimensions

Unit: mm (in.)

